

Redni broj / Ordinal number	Opis / Description	Upisati naziv/oznaku proizvoda i/ili modela / Enter the name / product label and / or model	Mjerna jedinica / Unit	Količina / Quantity	Cijena / Price	Ukupno bez PDV-a / Amount without VAT
1.	<p>Stroj za spajanje ceradnog platna 1 / <i>Tarpaulin canvas welding machine 1</i> Potrebna snaga - slobodan rad: 1,3 kW / <i>power requirement - free running: 1,3 kW</i> Snaga zahtjeva - max/h: 5,5 kW/h / <i>power requirement - max: 5,5 kW</i></p> <p>HF snage na elektrodi 8 kW/300 cm² / <i>HF power at electrode 8 kW/300 cm²</i> Glavni osigurač: 32 A / <i>Main fuse: 32 A</i> Standardni napon 3 x 400 V 50 Hz + neutralna + zemlja / <i>Standard voltage 3 x 400 V 50 Hz + neutral + earth</i></p> <p>radna frekvencija 27,12 MHz +/- 0,6% / <i>working frequency 27,12 MHz +/- 0,6%</i> maksimalno zavarivanje površine svakog radnog ciklusa: 300 cm² / <i>max. welding surface each working cycle: 300 cm²</i> maksimalna širina zavrivačke elektrode: 200 mm / <i>max. weldable electrode width: 200 mm</i> površina za zavarivanje: min 300 cm² / <i>weld area: minimal 300 cm²</i> pristup s 3 strane za optimizirano rukovanje materijalom/3-side access for optimized material handling držač elektroda (zračno hlađenje) 1200 mm / <i>air cooled electrode holder 1200 mm</i> 1200x150 mm zemaljski kondenzator montiran iza zavarivačke elektrode / <i>1200 x 150 mm capacitor mounted behind the welding electrode</i></p> <p>stol za zavarivanje 1445 mm x 635 mm s dodatkom 405x115 mm / <i>welding table 1445 mm x 635 mm with through 405 x 115 mm</i> valjci za tablice za smanjenje trenja, montirani na sve 4 strane stola stola za zavarivanje / <i>friction reducing table rollers, mounted on all 4 sides of the welding table</i> pedala za podizanje i spuštanje držača elektroda / <i>foot pedal, for up/down movement of electrode holder</i> početak ciklusa zavarivanja sa 4 ruke / <i>4 hand start</i></p> <p>1 dvostruka zavarivačka elektroda 1200 mm x 10 mm, podesiva 150-200 mm / <i>1 Double welding electrode 1200 mm x 10 mm, adjustable 150-200 mm</i> kotači za lako kretanje i postavljanje stroja / <i>wheels, to easy movement and positioning of machine</i> zavarivačka elektroda 1000 mm x 3 mm s držačem / <i>knife welding electrode 1000 mm x 3 mm with holder</i> donja stopna elektroda 1000 mm x 5 mm s izolacijskim materijalom / <i>bottom stop electrode 1000 mm x 5 mm with insulating material</i> C-šasija, dubina 750 mm / <i>C-chassis, depth 750 mm</i></p> <p>elektronički kontrolirani regulator zraka (max tlak 1400 kg na 7 bara) / <i>electronically controlled pressure regulator (max. Pressure 1400 kg at 7 bar)</i> zaštita od kratkog spoja / <i>flashover protection</i> Specifikacije softvera / <i>Software specification</i> program za sigurnost i upozorenje koji isključuje stroj ako ne ostane u postavljenoj snazi tijekom ciklusa zavarivanja / <i>safety and warning program, which turns off the machine if it does not stay within the set power value during the welding cycle</i> program osigurava kvalitetu zavarivanja i izbjegava nepotrebnu štetu na materijalu / <i>program ensures the quality of the weld and makes sure that unnecessary damage on material is avoided</i> program omogućuje spremanje do 4 zavarivanja / <i>program enables possibility to save up to 4 welding setups</i></p> <p>Pakiranje / <i>Packing</i> Osiguranje tereta i prijevoza / <i>Freight and transport insurance</i> Instalacija i obuka / <i>installation and training</i></p>		kom / piece	1		0,00
2.	<p>Stroj za spajanje ceradnog platna 2 / <i>Tarpaulin canvas welding machine 2</i> rukovanje velikim dimenzijama materijala / <i>simplified handling of large material volumes</i> fiksirana glava stroja / <i>fixed machine head</i> Potrebna snaga - slobodan rad: 0,65kW / <i>power requirement - free running: 0,65 kW</i> Snaga zahtjeva - max: 22 kW / <i>power requirement - max: 22 kW</i> emitirana snaga HF max na elektrodi: 12 kW / <i>emitted power HF max. on electrode: 12 kW</i> Glavni osigurač: 32 A / <i>Main fuse: 32 A</i> Standardni napon 3 x 400 V 50 Hz / <i>Standard voltage 3 x 400 V 50 Hz</i></p> <p>radna frekvencija 27,12 MHz +/- 0,6% / <i>working frequency 27,12 MHz +/- 0,6%</i> Podesivi tlak: max 1400 kg / <i>adjustable pressure: max 1400 kg</i> Pritisak zraka: min 7 bara / <i>air pressure: min 7 bar</i></p>		kom / piece	1		0,00

Maksimalna potrošnja zraka - automatski: 170 l/min / *Max air consumption - automatic: 170 l/min*

Duljina držača elektroda: 1000 mm / *length of electrode holder: 1000 mm*
površina za zavarivanje: min 500 cm² / *weld area: minimal 500 cm²*
stroj se prikida kada dođe do poremećaja električne struje i/ili komprimiranog zraka i pritisak se vraća u početni položaj / *the machine cuts out when there is a disruption of the electric current and/or the compressed air, and the press returns to the starting position*

računalo s mogućnošću predprogramiranja 1000 postupaka zavarivanja / *PC with possibility to pre-program 1000 welding procedures*
dimenzije stola za zavarivanje: 1200 x 900 mm (opremljen s valjcima na svim stranama stola za zavarivanje) / *1200 x 900 mm (equipped with rollers on all sides of the welding table)*

Specifikacije softvera / Software specification

program za nadzor energije koji automatski postavlja parametre za tlak i vrijeme zavarivanja / *energy monitoring program which automatically sets the parameters for pressure and welding time*

program za sigurnost i upozorenje koji isključuje stroj ako ne ostane u postavljenoj snazi tijekom ciklusa zavarivanja / *safety and warning program, which turns off the machine if it does not stay within the set power value during the welding cycle*

program koji omogućuje pohranu do 1000 zavarivanja / *program which enables possibility to save up to 1000 welding setups*

program za praćenje u stvarnom vremenu koji omogućuje brzo prepoznavanje slabih točaka i uskih grla / *program for real time monitoring system which allow quick identification of weak points and bottlenecks*

Pakiranje / Packing

Osiguranje tereta i prijevoza / Freight and transport insurance

Instalacija i obuka / installation and training

Cijena bez PDV-a / <i>Price without VAT</i>	UPISATI VALUTU (HRK ili EUR)/ENTER THE CURRENCY (HRK or EUR):	0,00
Iznos PDV-a / <i>VAT amount</i>	UPISATI VALUTU (HRK ili EUR)/ENTER THE CURRENCY (HRK or EUR):	0,00
Cijena s PDV-om / <i>Price with VAT</i>	UPISATI VALUTU (HRK ili EUR)/ENTER THE CURRENCY (HRK or EUR):	0,00

U/in _____, ____/____/____

MP / L.S.

potpis ovlaštene osobe ponuditelja / *signature of authorised representative of the Tenderer*